

# MityLite 2430NVG

[www.pelicanproducts.us](http://www.pelicanproducts.us)







## MityLite™ 2340NVG Flashlight

This compact flashlight has the same features of the [MityLite™ 2340 Flashlight](#) but equipped with a special lens that alters the color spectrum and cut the candlepower to preserve night vision.

## MityLite™ 2340NVG Flashlight Specifications

	High
<b>LIGHT SOURCE</b>	Xenon
<b>BATTERIES</b>	2 AA Alkaline (Included in select packaging)
<b>CHARGE TIME</b>	N/A
<b>VOLTAGE</b>	3
<b>LENGTH</b>	6.25" (15.9 cm)
<b>WEIGHT w/ BATTERIES</b>	3.5 oz. (0.1 kg)
<b>WEIGHT w/o BATTERIES</b>	1.86 oz. (0.05 kg)

	FL1 STANDARD	High
<b>LIGHT OUTPUT</b>		0 LUMENS
<b>RUNTIME (hours/min)</b>		
<b>BEAM DISTANCE (meters)</b>		
<b>PEAK BEAM INTENSITY (candela)</b>		






## MityLite™ 2340NVG Flashlight Configurations

Cat. #	Description
2340NVG	MityLite™ 2340NVG Flashlight (Boxed)

## MityLite™ 2340NVG Flashlight Accessories

Cat. #	Description
722	Helmet Light Holder
750	Helmet Light Holder
760	Helmet Light Holder
770	Universal Helmet Light Holder
2304	MityLite™ 2340NVG Lamp Module
2357	Cordura® Holster

## MityLite™ 2340NVG Flashlight Approvals

	Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.
	Class I, Div. 2; Gp. ABCD, T3A.
	10C-637-0
	Ex ib e IIC T4 IP67 IEC Ex TSA06.0021X
	Class I, Div. 1; Gps.C,D T3, Conforms to STD UL783